

SHSCam – Sensor head overview (355 – 1064 nm)

SHSCam Model	Detection area	Lateral resolution /microlenses	Greyscale	Camera bus	Evaluation rate (typical)	Wavelength range 355 – 800nm	Wavelength range 800 – 1064nm
AR3-130-GE	4.9 x 3.7 mm ²	37 x 27	12 bit	GigE	30 Hz	+	
AR3-075-GE	4.9 x 3.7 mm ²	65 x 49	12 bit	GigE	26 Hz	+	
AR3-075-GE NIR	4.9 x 3.7 mm ²	65 x 49	12 bit	GigE	26 Hz		+
HR2-130-GE*	11.2 x 7.0 mm ²	85 x 53	12 bit	GigE	20 Hz	+	
HR3-075-GE	8.4 x 7.0 mm ²	111 x 93	12 bit	GigE	10 Hz	+	
HR3-075-GE NIR	8.4 x 7.0 mm ²	111 x 93	12 bit	GigE	10 Hz		+
SHR4-130-GE	10.3 x 10.3 mm ²	79 x 79	12 bit	GigE	9 Hz	+	
SHR4-075-GE	10.3 x 10.3 mm ²	137 x 137	12 bit	GigE	6 Hz	+	
SHR4-075-GE NIR	10.3 x 10.3 mm ²	137 x 137	12 bit	GigE	6 Hz		+
UHR3-130-GE	15.2 x 15.2 mm ²	117 x 117	12 bit	GigE	7 Hz	+	
UHR3-075-GE	15.2 x 15.2 mm ²	203 x 203	12 bit	GigE	4 Hz	+	
UHR3-075-GE NIR	15.2 x 15.2 mm ²	203 x 203	12 bit	GigE	4 Hz		+
XHR2-110-GE	36.4 x 27.6 mm ²	331 x 251	12 bit	GigE	~1 Hz	+	
XHR2-110-GE NIR	36.4 x 27.6 mm ²	331 x 251	12 bit	GigE	~1 Hz		+

* Also available with USB3.0 camera bus

SHSCam – UV/DUV Sensor head overview (193 - 405 nm)

SHSCam Model	Detection area	Lateral resolution /microlenses	Greyscales	Camera bus	Evaluation rate (typical)	Wavelength range 193 – 365nm	Wavelength range 266 – 405nm
SHR6-130-GE DUV	12.2 x 12.2 mm ²	93 x 93	12 bit	GigE	4.5 Hz	+	
HR3-130-GE UV	8.4 x 7.0 mm ²	63 x 53	12 bit	GigE	24 Hz		+
UHR3-130-GE UV	15.2 x 15.2 mm ²	117 x 117	12 bit	GigE	7 Hz		+

SHSCam – SWIR Sensor head overview (980 - 1700 nm)

SHSCam Model	Detection area	Lateral resolution /microlenses	Greyscales	Camera bus	Evaluation rate (typical)	Cooling
SWIR-210-GE	9.6 x 7.6 mm ²	45 x 35	14 bit	GigE	30 Hz	Sensor thermoelectric cooling, camera passive air cooling
SWIR-350-GE	15.9 x 12.7 mm ²	45 x 35	14 bit	GigE	30 Hz	Sensor thermoelectric cooling, camera passive air cooling